

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>DVX P SERIES</b>			
<b>DVX P8</b>	2-way passive speaker, 1x8" woofer with 2" VC, 1 x 1" Neodymium compression driver with 1.5" VC, rotatable plastic CD-Horn (90°x70°), 300W/RMS, 75Hz-20KHz, 125 dB SPL, Dimensions 250x425x260mm, weight 9.8kg/21.6lbs.	<b>4.404,00</b>	<b>5.505,00</b>
<b>DVX P10</b>	2-way passive speaker, 1x10" woofer with 2" VC, 1 x 1" Neodymium compression driver with 1.5" VC, rotatable plastic CD-Horn (90°x70°), 300W/RMS, 70Hz-20KHz, 127 dB SPL, Dimensions 290x510x310mm, weight 12.5kg/27.6lbs.	<b>4.892,00</b>	<b>6.115,00</b>
<b>DVX P12</b>	2-way passive speaker, 1x12" woofer with 3" VC, 1 x 1.4" Neodymium compression driver with 2.5" VC, rotatable plastic CD-Horn (90°x70°), 500W/RMS, 90Hz-20KHz, 133 dB SPL, Dimensions 370x625x395mm, weight 23.2kg/51.1lbs.	<b>6.988,00</b>	<b>8.735,00</b>
<b>DVX P15</b>	2-way passive speaker, 1x15" woofer with 3" VC, 1 x 1.4" Neodymium compression driver with 2.5" VC, rotatable plastic CD-Horn (90°x40°), 500W/RMS, 60Hz-20KHz, 133 dB SPL, Dimensions 430x690x450mm, weight 26.1kg/57.5lbs.	<b>7.616,00</b>	<b>9.520,00</b>
<b>DVX P215</b>	Passive speaker, 2x15" woofer with 3" VC, 1 x 1.4" Neodymium compression driver with 2.5" VC, rotatable plastic CD-Horn (90°x40°).	<b>12.224,00</b>	<b>15.280,00</b>
<b>DVX PSW15</b>	Passive subwoofer, 1x15" woofer with 3" VC, 1000W Peak power, 500W/RMS, 35Hz-200Hz, 132 dB SPL, Dimensions 470x627x600mm, weight 30.9kg/68.1lbs.	<b>5.588,00</b>	<b>6.985,00</b>
<b>DVX PSW18</b>	Passive subwoofer, 1x18" woofer with 4" VC, 2000W Peak power, 1000W/RMS, 28Hz-200Hz, 134 dB SPL, Dimensions 565x710x700mm, weight 44.1kg/97.2lbs.	<b>7.476,00</b>	<b>9.345,00</b>
<b>DVX PSW218</b>	Passive subwoofer, 2x18" woofer with 4" VC, 4000W Peak power, 2000W/RMS, 28Hz-200Hz, 140 dB SPL, Dimensions 565x1207x700mm, weight 74.2kg/163lbs.	<b>12.924,00</b>	<b>16.155,00</b>
<b>INGENIA SERIES</b>			
<b>IG1T</b>	2-way Active Speaker 2x6.5" neo woofers, 1" comp. driver, 400W digipro® G3, max SPL 128 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 195x536x271mm (7.68x21.10x10.67in), Weight 10,8Kg – 23.81lbs.	<b>6.988,00</b>	<b>8.735,00</b>
<b>IG2T</b>	2-way Active Speaker 2x8" neo woofers, 1" comp. driver, 400W digipro® G3, max SPL 128 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 228x646x315mm (8.98x25.43x12.40in), Weight 12,8Kg – 28.22lbs.	<b>7.684,00</b>	<b>9.605,00</b>
<b>IG3T</b>	2-way Active Speaker 2x10" neo woofers, 1.4" comp. driver, 900W/RMS digipro® G3, max SPL 132 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 280x806x393mm (11.02x31.73x15.47in), Weight 20,8Kg – 45.86lbs.	<b>10.756,00</b>	<b>13.445,00</b>
<b>IG4T</b>	2-way Active Speaker 4x6.5" neo woofers, 1.4" comp. driver, 900W/RMS digipro® G3, max SPL 132 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 195x956x271mm (7.68x37.64x10.67in), Weight 18,2Kg – 40.12lbs.	<b>11.456,00</b>	<b>14.320,00</b>
<b>IG4T WHITE</b>	2-way Active Speaker 4x6.5" neo woofers, 1.4" comp. driver, 900W/RMS digipro® G3, max SPL 132 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 195x956x271mm (7.68x37.64x10.67in), Weight 18,2Kg – 40.12lbs.	<b>11.456,00</b>	<b>14.320,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>ES SERIES</b>			
<b>ES 503</b>	3-amped 1000 W stereo sound system. 2x tops with 4x 3" full-range speakers with logarithmic position, double-ringed phase plug and vertical digital steering. 1x 12" active subwoofer. 3 inputs, Bluetooth, Mix out, OLED display with advanced user interface.	<b>5.800,00</b>	<b>7.250,00</b>
<b>ES 503 WHITE</b>	3-amped 1000 W stereo sound system. 2x tops with 4x 3" full-range speakers with logarithmic position, double-ringed phase plug and vertical digital steering. 1x 12" active subwoofer. 3 inputs, Bluetooth, Mix out, OLED display with advanced user interface. WHITE	<b>5.800,00</b>	<b>7.250,00</b>
<b>ES 802</b>	Bi-amped 1200 W system. 2x tops with 4x 3" full-range speakers with logarithmic position, double-ringed phase plug and vertical digital steering. 1x 12" active subwoofer.	<b>4.876,00</b>	<b>6.095,00</b>
<b>ES 1002</b>	1800 W Active PA System. Sub and Top Cover included	<b>9.768,00</b>	<b>12.210,00</b>
<b>ES 1203</b>	2400W stereo system	<b>13.260,00</b>	<b>16.575,00</b>
<b>ES 1203 WHITE</b>	2400W stereo system. WHITE	<b>13.260,00</b>	<b>16.575,00</b>
<b>ES 1203 TOP</b>	Satelite speaker for ES 1203 system	<b>2.096,00</b>	<b>2.620,00</b>
<b>LVX SERIES</b>			
<b>LVX 8</b>	2-way Active Speaker with 400W Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 8" woofer with 1.5", VC 1" driver with rotatable asymmetric 90°/40°x60° horn, SPL peak 121 dB. Dimensions 260x420x260mm, Weight 9,5 Kg / 20,94 lbs.	<b>3.284,00</b>	<b>4.105,00</b>
<b>LVX 8W</b>	White version (no handles)	<b>3.284,00</b>	<b>4.105,00</b>
<b>LVX 10</b>	2-way Active Speaker with integrated 400W/RMS Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 10" woofer with 1.5"VC, 1" neodymium driver with rotatable asymmetric 90°/40°x60° horn, max SPL 125 dB. Dimensions 300x483x300mm, weight 12 Kg / 26,45 lbs.	<b>3.564,00</b>	<b>4.455,00</b>
<b>LVX 10W</b>	White version (no handles)	<b>3.564,00</b>	<b>4.455,00</b>
<b>LVX 12</b>	2-way Active Speaker with integrated 800W/RMS Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 12" woofer with 2"VC, 1" compression driver with rotatable 90°x40° horn, max SPL 127 dB. Dimensions 360x610x360mm, weight 16,5 Kg / 36,37 lbs.	<b>5.032,00</b>	<b>6.290,00</b>
<b>LVX 12W</b>	White version (no handles)	<b>5.032,00</b>	<b>6.290,00</b>
<b>LVX 15</b>	2-way Active Speaker with integrated 800W/RMS Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 15" woofer with 2"VC, 1" compression driver with rotatable 90°x40° horn, max SPL 128 dB. Dimensions 430x680x430mm, weight 20 Kg / 44,09 lbs.	<b>5.380,00</b>	<b>6.725,00</b>
<b>LVX 15W</b>	White version (no handles)	<b>5.380,00</b>	<b>6.725,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>LVX XM12</b>	2-way coaxial active monitor, with one 1" CD exit (1.4" voice coil) and one 12" woofer (2.5" voice coil), 600 W DIGIPRO® G3 class D amplifier, max 127 dB SPL, DSP 56 bit, AD/DA Converter: 24 bit / 48 kHz, horn coverage (HxV) 90 x 70°, 8 preset configurations, mic/line switch, Cabinet: Plywood with black pvc cover. Dimensions: 515x460x 370 mm, Weight: 20,1 kg (44,31 lb)	<b>6.288,00</b>	<b>7.860,00</b>
<b>LVX XM15</b>	2-way coaxial active monitor, with one 1" CD exit (1.4" voice coil) and one 15" woofer (2.5" voice coil), 600 W DIGIPRO® G3 class D amplifier, max 128 dB SPL, DSP 56 bit, AD/DA Converter: 24 bit / 48 kHz, horn coverage (HxV) 90 x 70°, 8 preset configurations, mic/line switch, Cabinet: Plywood with black pvc cover, Dimensions: 635x460x 370 mm, Weight: 22,3 kg (49,16 lb)	<b>6.848,00</b>	<b>8.560,00</b>
<b>LVX P8</b>		<b>1.524,00</b>	<b>1.905,00</b>
<b>LVX P8 WHITE</b>		<b>1.524,00</b>	<b>1.905,00</b>
<b>LVX P10</b>		<b>1.664,00</b>	<b>2.080,00</b>
<b>LVX P10 WHITE</b>		<b>1.664,00</b>	<b>2.080,00</b>
<b>LVX P12</b>		<b>2.124,00</b>	<b>2.655,00</b>
<b>LVX P12 WHITE</b>		<b>2.124,00</b>	<b>2.655,00</b>
<b>LVX P15</b>		<b>2.532,00</b>	<b>3.165,00</b>
<b>LVX P15 WHITE</b>		<b>2.532,00</b>	<b>3.165,00</b>
<b>PVX PSW15</b>		<b>3.328,00</b>	<b>4.160,00</b>
<b>PVX PSW15 WHITE</b>		<b>3.328,00</b>	<b>4.160,00</b>
<b>LVX PSW18</b>		<b>3.984,00</b>	<b>4.980,00</b>
<b>LVX PSW18 WHITE</b>		<b>3.984,00</b>	<b>4.980,00</b>
<b>SIGMA SERIES</b>			
<b>Sigma S115</b>	2-way Active Speaker 15" woofer 1000W digipro® G2, 56 bit high resolution DSP, 46Hz - 20.000Hz, max SPL 133 dB, Dimensions: 590x765x533mm, Weight 33 Kg / 72,6 lbs.	<b>8.244,00</b>	<b>10.305,00</b>
<b>Sigma S215</b>	3-way Active Speaker 2x15" woofer +1.4" compression driver, 1400W digipro® G2, 56 bit high resolution DSP, 42Hz - 20.000Hz, max SPL 139 dB, Dimensions: 590x1215x533mm, Weight 50 Kg / 110 lbs.	<b>10.340,00</b>	<b>12.925,00</b>
<b>Sigma S118</b>	Active Subwoofer 18"/4" VC Bassreflex ,1400W, max SPL 134 dB, 56 bit high resolution DSP, 32Hz - 110Hz, Dimentions: 509x815x533, Weight 38 Kg / 83,6 lbs.	<b>8.244,00</b>	<b>10.305,00</b>
<b>Sigma S115F</b>	2-way Active Speaker 15" woofer 1000W digipro® G2, 56 bit high resolution DSP, 46Hz - 20.000Hz, max SPL 133 dB, Dimensions: 590x765x533mm, Weight 33 Kg / 72,6 lbs. Flyable	<b>9.080,00</b>	<b>11.350,00</b>
<b>Sigma S218</b>	Bass-reflex Subwoofer 2x18" .180W RMS.	<b>13.972,00</b>	<b>17.465,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>FLEXSYS SERIES</b>			
<b>F 212</b>	Selfpowered 2-way loudspeaker, integrated 750W/RMS digipro™ digital power, 2 x 12" high power woofers incl. ADC™ phase alignment, 1 x 1" RCF neodymium compression driver, rotatable 60°x40° horn, SPL max. 132 dB, 50Hz-20KHz, dimensions 360x930x500mm, weight 31,5 kg/69,44lbs	<b>9.640,00</b>	<b>12.050,00</b>
<b>F 315</b>	Selfpowered 3-way loudspeaker, integrated 750W/RMS digipro™, 1 x 15" high power woofer, 1x 6" hornloaded mid range driver, 1 x 1" compression driver, rotatable 90°x40° CD-Horn, 12 x M10 rigging points, SPL max. 131 dB, 47Hz-20KHz, dimensions 440x880x500mm, weight 31 kg/68,2lbs	<b>10.340,00</b>	<b>12.925,00</b>
<b>FM 8</b>	Coaxial Active 8"/1" Stage Monitor, 100W/RMS bi-amp digipack, 24-Bit DSP incl. 8 Presets, 117dB Max. SPL, Pole Mount, Dimensions: 280x290x410mm, Weight: 9,8kg	<b>2.516,00</b>	<b>3.145,00</b>
<b>FM 10</b>	Coaxial Active 10"/1" Stage Monitor, 200W/RMS bi-amp digipack, 24-Bit DSP incl. 8 Presets, 120dB Max. SPL, Pole Mount, Dimensions: 370x290x410mm, 12,8kg	<b>2.796,00</b>	<b>3.495,00</b>
<b>FM 12</b>	Coaxial Active 12"/1" Stage Monitor, 300W/RMS bi-amp digipack, 24-Bit DSP inkl. 8 Presets, 120dB Max. SPL, Pole Mount, Dimensions: 450x290x410mm, 17kg	<b>3.564,00</b>	<b>4.455,00</b>
<b>FMX 10</b>		<b>2.992,00</b>	<b>3.740,00</b>
<b>FMX 12</b>		<b>3.648,00</b>	<b>4.560,00</b>
<b>FMX 15</b>		<b>4.320,00</b>	<b>5.400,00</b>
<b>SYA Series</b>			
<b>SYA 10</b>		<b>2.000,00</b>	<b>2.500,00</b>
<b>SYA 12</b>		<b>2.320,00</b>	<b>2.900,00</b>
<b>SYA 15</b>		<b>2.656,00</b>	<b>3.320,00</b>
<b>OPERA SERIES</b>			
<b>OPERA 10</b>	2 way active speaker 10" woofer, 600W RMS, max SPL 128 dB, asymmetrical CD horn, Dimensions: 300x552x301 mm, weight: 12.3 kg (27.12 lbs.)	<b>2.724,00</b>	<b>3.405,00</b>
<b>OPERA 12</b>	2 way active speaker 12" woofer, 600W RMS, max SPL 129 dB, asymmetrical CD horn, Dimensions: 350x642x349 mm, weight: 14.3 kg (31.53 lbs.)	<b>3.004,00</b>	<b>3.755,00</b>
<b>OPERA 15</b>	2 way active speaker 15" woofer, 600W RMS, max SPL 130 dB, asymmetrical CD horn, Dimensions: 420x722x419 mm, weight: 18.3 kg (40.34 lbs.)	<b>3.356,00</b>	<b>4.195,00</b>
<b>Opera P15</b>	2-way Passive Speaker 15" woofer, 1" HF driver, 400w RMS, 800w PRG. Max SPL 128dB. Driver Protection PTC, Directivity 80°/65° x 60° asymmetrical CD Horn. Crossover Frequency (passive) 2100Hz. Dimensions 432x665x353 mm, Weight 18,4KG.	<b>2.864,00</b>	<b>3.580,00</b>
<b>OPERA UNICA SERIES</b>			
<b>OPERA UNICA 12</b>	dBTechnologies' flagship active loudspeaker turns into the most complete professional system thanks to networkable capability and complete EQ control via Aurora Net control software	<b>5.172,00</b>	<b>6.465,00</b>
<b>OPERA UNICA 15</b>	dBTechnologies' flagship active loudspeaker turns into the most complete professional system thanks to networkable capability and complete EQ control via Aurora Net control software	<b>5.868,00</b>	<b>7.335,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>B-HYPE SERIES</b>			
<b>B-Hype 8</b>	The new B-HYPE 8 is a versatile active speaker. It is equipped with one 1" compression driver (1" voice coil), and one 8" woofer (1.5" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>1.036,00</b>	<b>1.295,00</b>
<b>B-Hype 10</b>	The new B-HYPE 10 is a versatile active speaker. It is equipped with one 1" compression driver (1" voice coil), and one 10" woofer (1.5" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>1.384,00</b>	<b>1.730,00</b>
<b>B-Hype 12</b>	The new B-HYPE 12 is a versatile active speaker. It is equipped with one 1" neodymium compression driver (1" voice coil), and one 12" woofer (2" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>1.736,00</b>	<b>2.170,00</b>
<b>B-Hype 15</b>	The new B-Hype 15 is a versatile active speaker. It is equipped with one 1" neodymium compression driver (1" voice coil), and one 15" woofer (2" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>2.084,00</b>	<b>2.605,00</b>
<b>B-HYPE MOBILE HT</b>	B-Hype M mixes the professional acoustic performance of the B-H family with the most advanced versatility of a complete portable PA equipped with a wireless microphone system, audio media player with Bluetooth connection, SD card and USB port, a long lasting battery, wheels and a retractable top handle	<b>3.356,00</b>	<b>4.195,00</b>
<b>B-HYPE MOBILE BT</b>	B-Hype M mixes the professional acoustic performance of the B-H family with the most advanced versatility of a complete portable PA equipped with a wireless microphone system, audio media player with Bluetooth connection, SD card and USB port, a long lasting battery, wheels and a retractable top handle	<b>3.356,00</b>	<b>4.195,00</b>
<b>SUB SERIES</b>			
<b>SUB 15H</b>	Semi horn-loaded active 15" Subwoofer, 1000W/PRG digipro™G3 digital power amp, integrated delay (up to 4.5 ms), active stereo X-Over with switchable frequency 90/120Hz, Phase inversion switch, USB port (service data), SMPS with auto-range, 133 dB SPL, 35-150Hz, Dimensions: 524x511x695mm, weight 31.5 kg/69.4lbs	<b>7.476,00</b>	<b>9.345,00</b>
<b>SUB 18H</b>	Semi horn-loaded active 18" Subwoofer, 1500W/PRG digipro™G3 digital power amp, integrated delay (up to 4.5 ms), active stereo X-Over with switchable frequency 90/120Hz, Phase inversion switch, USB port (service data), SMPS with auto-range, 134 dB SPL, 28-150Hz, Dimensions: 524x711x695mm, weight 41.4 kg/91.3lbs	<b>9.500,00</b>	<b>11.875,00</b>
<b>SUB 612</b>	Just like 15" and 18" models of the family, bass-reflex SUB 612 features a 600W RMS Class-D Power Amplifier with SMPS, delivers outstanding sound pressure levels in spite of a very compact housing (only 19.8 Kg -43,65 lbs) and provides an impressively precise low-end reproduction.	<b>2.780,00</b>	<b>3.475,00</b>
<b>SUB 615</b>	SUB615 is a bass-reflex active subwoofer featuring a 600W RMS Class D SMPS Power Amplifier and is equipped with a 15" transducer.	<b>3.828,00</b>	<b>4.785,00</b>
<b>SUB 618</b>	SUB618 is a bass-reflex active subwoofer featuring a 600W RMS Class D Power Amplifier with SMPS and is equipped with a 18" transducer.	<b>4.876,00</b>	<b>6.095,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>SUB 28D</b>	Active Bandpass Subwoofer 2x8" woofer, 400W/RMS, Class D Digipack , 45Hz - 150Hz , max SPL 125 dB , 24 bit DSP with stereo X-Over, Dimensions: 290x520x505, Weight: 19,5 Kg	<b>3.844,00</b>	<b>4.805,00</b>
<b>SUB 915</b>		<b>7.476,00</b>	<b>9.345,00</b>
<b>SUB 918</b>		<b>9.500,00</b>	<b>11.875,00</b>
<b>MINIBOX SERIES</b>			
<b>K 70</b>	Compact Active Speaker 1x 5" dB Bass + Tweeter, 100 W / Music, 50 W / RMS, 101 dB SPL max, 100 – 16.000Hz, Dimensions 170x270x185 mm, Weight 3,5 Kg	<b>1.188,00</b>	<b>1.485,00</b>
<b>K 162</b>	Compact Active Speaker 2x 6,5" dB Bass + Tweeter, 130 W / Music, 65 W / RMS, 110 dB SPL max, 85 – 19.000 Hz, Dimensions 210x350x270mm, Weight 5,5 Kg	<b>1.400,00</b>	<b>1.750,00</b>
<b>K 300</b>	Compact Active Speaker 2x 6,5" neodymium woofer with 1,5" VC, 1" neodymium driver, Class-D Bi-Amp 120 W/RMS, max. SPL peak 118 dB, Dimensions 210x350x270 mm, weight 5 Kg/11,02 lbs.	<b>2.308,00</b>	<b>2.885,00</b>
<b>L 160 D</b>		<b>1.956,00</b>	<b>2.445,00</b>
<b>L 80 D</b>	Compact Active Speaker 1x 4" woofer, 1x 4" coaxial woofer with 1" dome tweeter, 80 W digipack, DSP with 8 presets, use as monitor (35° angle). Line Balanced Input with XLR and 1/4" jack (in parallel). RCA aux input for CD, DAT, MP3 players, etc. Mic/Line sensitivity switch. Line input volume and Aux volume. Dimensions: (WxHxD) 155x265x180 mm - 6.10x10.43x7.09 in.	<b>1.680,00</b>	<b>2.100,00</b>
<b>HPA AMPLIFIERS</b>			
<b>HPA 3100</b>	Class-HD power amp with switch-mode supply, 2 x 1700W @ 2 Ohms, 2 x 1200W @ 4 Ohms, 2 x 800W @ 8 Ohms, 1 x 3400W @ 4 Ohm, 1 x 2400W @ 8 Ohms, damping factor >300, slew rate 50V/μs, 2 x XLR-Input, 2 x XLR-Output, 2 x Speakon-Output, 19", 2U, 482x89x420mm, weight 14 kg/30,86lbs	<b>6.848,00</b>	<b>8.560,00</b>
<b>A2TI</b>		<b>3.648,00</b>	<b>4.560,00</b>
<b>A4TI</b>		<b>4.584,00</b>	<b>5.730,00</b>
<b>CONTROLLERS</b>			
<b>AC26N</b>	Digital Audio Processor, 2 in - 6 out, Full Range power supply, RDNet Hardware Interface, USB interface, remotable via RDNet or USB. Max input level 21dBu (without pad) / 27dBu (with -6dB pad). Max output level 21dBu. DSP Processing: 28/56bit - 48Khz. A/D and D/A Converts: 24bit - 96Khz.	<b>5.660,00</b>	<b>7.075,00</b>
<b>ASX 24</b>	2-Way/3-Way stereo - 4-Way Mono Active Crossover. 2x XLR-Input with 25Hz high-pass filter switch, 6x XLR-Output, high quality 24dB/octave slope Linkwitz-Riley filters, In/Out level controls, xover frequency selection fo all bands, mute key and phase reversal for each band, adjustable delay time up to 2ms for outputs, "LOW SUM" function to convey the whole LF range of L&R channels to a mono sub out, multiband limiter with adjustable threshold.	<b>1.400,00</b>	<b>1.750,00</b>
<b>DSX 2040</b>	Digital 2 in 4 controller, 48Khz/32-bit signal processing, dynamic range >110dB(A), 3000ms total delay, 4 parameter. EQs per in- and output, programmable x-over and routing-section , editable limiter per output, large LC-Display, bank for 30 presets , USB-interface for programming and data-transfer, 19", 1U, in- and outputs on balanced XLR.	<b>7.128,00</b>	<b>8.910,00</b>
<b>Switch 6</b>	2 x XLR-Input into 2x6 XLR-Output, 1 Unit with LED Display and Remote Control. Up to 6 units in parallel mode.	<b>3.424,00</b>	<b>4.280,00</b>



# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>RADIO SYSTEMS</b>			
<b>MOVING D RX</b>	Digital wireless system receiver with 320MHz operating bandwidth (a single systems uses at the same time the whole UHF band - from 470 to 790 MHz). More than 20 transmitters simultaneously. Frequency response: 35Hz to 19KHz ~ 3dB. Frequency band presets for each country: you only need to choose the country (through the on-board OLED display or via USB on the software for Windows7™/Windows8™) and the engine will calculate the proper frequencies. Revolutionary 4-level digital modulation system for higher amount of transmitted information (KBPS). Uncompressed CD-quality audio at 44.1KHz - 16bit. IrDA (infrared) Rx/Tx setup communication system. Sturdy construction for stage long-life. Low power consumption OLED display visible even in the dark. USB mini-B port to communicate with the dedicated PC software. XLR balanced and 1/4" jack unbalanced outputs. RJ11 connector for HUB 800 (optional) device connection, which allows remote controlling. 2x BNC connectors for antennas. External power supply 110 - 220Vac (included). Half 19" rack size, weight 750g.	<b>5.868,00</b>	<b>7.335,00</b>
<b>MOVING D-H</b>	Hand transmitter for MOVING-D digital wireless systems with Beyerdynamic TGX-58 cardioid capsule. Frequency response: 35Hz to 19KHz ~ 3dB. IrDA (infrared) Rx/Tx setup communication system. Sturdy construction for stage long-life. Very low handling noise. Low power consumption OLED display visible even in the dark. Audio Mute switch. Two AA batteries. Weight 350 (with batteries).	<b>2.796,00</b>	<b>3.495,00</b>
<b>MOVING D-B</b>	Bodypack transmitter for MOVING-D digital wireless systems with 3-Pin mini XLR connector. It can be used with headset, lavalier microphones, guitar/bass and other instruments. Frequency response: 35Hz to 19KHz ~ 3dB. IrDA (infrared) Rx/Tx setup communication system. Sturdy construction for stage long-life. Very low handling noise. Low power consumption OLED display visible even in the dark. Audio Mute switch. Two AA batteries. Weight 250 (with batteries).	<b>2.656,00</b>	<b>3.320,00</b>
<b>TOURING RACK MO</b>	Professional touring rack including: 6x Moving D receivers, 1x AS6W Antenna Splitter, 1x HUB 800, 1x RPS10, XLR connectors for external connection	<b>41.908,00</b>	<b>52.385,00</b>